



Material cuplaj: fonta EN-GJ-250 UNI EN 1561

Material element elastic: cauciuc

Tip cuplaj	Cod cuplaj complet	Bucsa	Diametru ax		Dimensiuni								Greutate (kg)
			Min. (mm)	Max. (mm)	De (mm)	D (mm)	b (mm)	E (mm)	G (mm)	H <sub>2</sub> (mm)	B (mm)	H (mm)	
HRC 70	HRCE070	1008	9	25	69	60	31	25,0	18,0	20,0	23,5	65,0	0,88
HRC 90	HRCE090	1108	9	28	85	70	32	30,5	22,5	19,5	23,5	69,5	1,45
HRC 110	HRCE110	1610	14	42	112	100	45	45,0	29,0	18,5	26,5	82,0	3,20
HRC 130	HRCE130	1610	14	42	130	105	50	53,0	36,0	18,0	26,5	89,0	4,54
HRC 150	HRCE150	2012	14	50	150	115	62	60,0	40,0	23,5	33,5	107,0	6,60
HRC 180	HRCE180	2517	16	60	180	125	77	73,0	49,0	34,5	46,5	142,0	10,75
HRC 230	HRCE230	3020	25	75	225	155	99	85,5	59,5	39,5	52,5	165,0	19,14
HRC 280	HRCE280	3525	35	100	275	206	119	106,0	74,5	51,0	66,5	208,0	41,00