


3

ST-4



Galvanized

Stainless

UNC

-40 - +80 °C

RoHS

1

2

4

5

d ₁	h											d ₂	l	s _{min}
6	7	8	10	13	-	-	-	-	-	-	-	M3	6	0,8
8	6	8	10	13	15	-	-	-	-	-	-	M3	6	1
10	6	8	10	12	15	18	20	-	-	-	-	M4	10	1,2
15	6	8	10	12	15	20	25	-	-	-	-	M4	10	1,4
18	6	7,5	8,5	10	13	15	-	-	-	-	-	M6	18	2
20	6	8	10	13	15	20	25	30	-	-	-	M6	18	2
25	6	8	10	15	20	25	30	40	-	-	-	M6	18	2
30	6	8	10	15	20	25	30	35	40	-	-	M8	20	2
40	8	10	15	20	25	30	35	40	45	50	-	M8	23	2
50	10	15	20	25	30	35	40	45	50	60	-	M10	28	2
60	15	20	25	30	35	40	45	50	60	-	-	M10	28	2
70	20	25	30	35	40	45	50	55	60	70	-	M10	27	3
75	20	25	30	35	40	45	50	55	60	70	-	M12	37	3
80	17	30	40	50	60	80	-	-	-	-	-	M12	37	3
100	25	30	35	40	45	50	55	60	75	100	-	M16	41	3
125	40	55	60	70	75	100	125	-	-	-	-	M16	41	3
150	45	50	55	60	75	100	120	150	-	-	-	M16	41	4
164	75	-	-	-	-	-	-	-	-	-	-	M16	41	4
200	100	-	-	-	-	-	-	-	-	-	-	M20	40	5

Appearance

- Elastomer (default natural rubber, NK)**
 - Operation temperature -40 - +80 °C
 - Should not be used at oil, alkaline, acid
 - You can find other opportunities at the Elastomer

6

- Hardness (default 55 +/-5 Shore A)**

- 43 (soft)
- 55 (medium)
- 72 (hard)

7

- Metal insert**

- ST37 (galvanized, DIN EN 12329 – Fe//Zn12//A)
- A2 (stainless, AISI 304)
- A4 (stainless, AISI 316)

8

Use

Perfect for absorbing vibration generated by pumps, fans, washing machines, electric engines, control cabinets and other industrial and agricultural equipments.

Advantages: easy to assemble, high flexibility, economy, long life.

Cylindrical vibration dampers

1 2 3 4 5 6 7 8
40/30-4 M8x23 NK 55 +/-5 SH A, ST37

- 1 Diameter (d₁)
- 2 Height (h)
- 3 Type
- 4 Thread size (d₂)
- 5 Thread length (l)
- 6 Elastomer
- 7 Hardness
- 8 Metal quality