





Material cuplaj: fonta EN-GJ-250 UNI EN 1561

Material element elastic: cauciuc

Tip cuplaj	Cod cuplaj complet	Dimensiuni										Greutate (kg)
		Alezaj standard (mm)	Ax maxim permis (mm)	De (mm)	D (mm)	b (mm)	E (mm)	G (mm)	H ₂ (mm)	B (mm)	H (mm)	
HRC 70	HRCP070	10	32	69	60	31	25,0	18,0	20,0	23,5	65,0	1,20
HRC 90	HRCP090	10	42	85	70	32	30,5	22,5	26,0	30,0	82,5	2,15
HRC 110	HRCP110	10	55	112	100	45	45,0	29,0	37,0	45,0	119,0	6,10
HRC 130	HRCP130	14	60	130	105	50	53,0	36,0	47,0	55,5	147,0	8,90
HRC 150	HRCP150	19	70	150	115	62	60,0	40,0	50,0	60,0	160,0	12,20
HRC 180	HRCP180	35	80	180	125	77	73,0	49,0	58,0	70,0	189,0	18,40
HRC 230	HRCP230	38	100	225	155	99	85,5	59,5	77,0	90,0	239,5	35,50
HRC 280	HRCP280	48	130	275	206	119	105,5	74,5	90,0	105,5	285,5	71,50