







MVE - Standard Range

► 2 POLES
3000-3600 rpm

TYPE	Mechanical Features						Electric Features													
	Working moment (*)		FC		Weight		Power		Current				Temp. Class Dust (°C)	Cable Glande						
	Kgcm		Kg		Kg		Kw		A max (Y)		Ia/In									
	50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	50 Hz	60 Hz	50 Hz	60 Hz	50Hz	60Hz								
MVE 60/3	1.35	0.82	68	59	4.2		0.08	0.09	0.16	0.18	3.0	3.0	100	M16						
MVE 100/3	2.01	1.52	101	110	4.6		0.1	0.11	0.19	0.18	3.0	3.0	100	M16						
MVE 200/3	3.72	2.61	187	189	7.0		0.18	0.21	0.35	0.35	3.3	3.30	100	M20						
MVE 202/3	3.72	2.61	187	189	7.2		0.18	0.21	0.35	0.35	3.3	3.30	100	M20						
MVE 300/3	6.39	4.46	321	323	9.8		0.27	0.28	0.52	0.45	3.60	3.50	100	M20						
MVE 400/3	7.96	5.68	407	411	10.3		0.30	0.36	0.58	0.60	3.50	3.50	100	M20						
MVE 500/3	10.27	7.38	530	534	15.8		0.50	0.58	0.96	0.97	4.00	4.20	100	M20						
MVE 700/3	14.90	10.57	758	765	16.5		0.66	0.75	1.25	1.24	4.30	5.00	100	M20						
MVE 800/3	15.68	11.06	794	800	20.6		0.75	0.90	1.45	1.50	3.80	3.80	100	M20						
MVE 1200/3	20.26	14.00	1005	1013	21.6		0.95	1.15	1.85	1.95	4.40	4.50	100	M20						
MVE 1300/3	27.58	18.86	1355	1365	22.0		1.30	1.38	2.44	2.25	5.20	5.00	100	M20						
MVE 1301/3	27.58	18.86	1355	1365	30.3		1.30	1.38	2.44	2.25	5.20	5.00	100	M20						
MVE 1310/3	22.34	22.34	1123	1616	30.0		1.30	1.38	2.44	2.25	5.20	5.00	100	M20						
MVE 1600/3	31.26	22.22	1601	1608	51.6	51.2	1.57	1.60	2.94	2.61	5.90	6.20	135	M25						
MVE 2000/3	36.78	27.60	2027	1997	52.8	52.0	2.00	2.10	3.75	3.42	6.50	6.40	135	M25						
MVE 2300/3	45.97	31.87	2302	2306	53.6	51.6	2.40	2.45	4.44	3.94	6.00	6.30	135	M25						
MVE 3200/3	68.10	43.89	3252	3176	103.0	101.4	2.90	2.90	5.30	4.61	8.30	8.20	135	M32						
MVE 4000/3	79.40	55.99	4033	4052	107.0	103.8	2.90	2.90	5.30	4.61	8.5	9.7	135	M32						
MVE 5000/3	103.24	69.76	5009	5048	111.2	105.8	4.00	4.00	7.22	6.28	8.50	9.80	135	M32						

(*) = Working moment = 2 x static moment



Ex ISO T100°C resp T135°C – IP66
TUV NORD Statement Conformity Number TUV 05 ATEX 2768X
- Equipment and protective system intended for use in potentially explosive atmospheres (Zone 2) - Directive 94/9/EC
- Compliance with Essential Health and Safety Requirements
EN 61241-10



CE Declaration of conformity "type A" according to:
- 73/23/EEC - 98/37/EEC - EN 60034-1

Class II Div2 Group FG - T5 - NEMA 4 conform to UL 1836 and CSA C22.2 NO25
Intertek ETL - SEMCO

TYPE	Dimensional Features															
	FIG.															